

# UNITED FIRE EQUIPMENTS PRIVATE LIMITED

Manufacturers of **LIFEGUARD** brand. ISI Marked Fire Fighting Equipments

**AN ISO 9001 : 2015 CERTIFIED COMPANY**

OFFICE : Lifeguard Tower, K - 960, Rithala (Opp. SBI), Rohini, Delhi -110085

WORKS : B - 38, Mangolpuri Industrial Area, Phase-II, New Delhi - 110034

E-Mail - ufe126@gmail.com, Web Site : www.lifeguardindia.in

## PRICE LIST

w.e.f. Aug 01<sup>st</sup>, 2023

### POWDER PORTABLE FIRE EXTINGUISHERS STORED PRESSURE TYPE (IS: 15683)

S. No.	LG- CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-121	<b>Powder Fire Extinguisher (Stored Pressure type) Capacity 01 Kg</b> duly ISI marked conforming to <b>IS: 15683:2018</b> , with IS 4308, ISI marked ABC powder complete with squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: -30°C to + 60°C. <b>Brand LIFEGUARD</b>	8424/18%	1,750.00
2.	LG- 122	<b>Powder Fire Extinguisher (Stored Pressure type) Capacity 02 Kg</b> duly ISI marked conforming to <b>IS: 15683:2018</b> , with IS 4308, ISI marked ABC powder complete with squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: -30°C to + 60°C. <b>Brand LIFEGUARD</b>	8424/18%	2,100.00
3.	LG-124	<b>Powder Fire Extinguisher (Stored Pressure type) Capacity 04 Kg</b> duly ISI marked conforming to <b>IS: 15683:2018</b> , with IS 4308, ISI marked ABC powder complete with squeeze grip release valve, discharge pipe, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: -30°C to + 60°C. <b>Brand LIFEGUARD</b>	8424/18%	3,000.00
4.	LG-126	<b>Powder Fire Extinguisher (Stored Pressure type) Capacity 06 Kg</b> duly ISI marked conforming to <b>IS: 15683:2018</b> , with IS 4308, ISI marked ABC powder complete with squeeze grip release valve, discharge pipe, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: -30°C to + 60°C. <b>Brand LIFEGUARD</b>	8424/18%	3,625.00
5.	LG-129	<b>Powder Fire Extinguisher (Stored Pressure type) Capacity 09 Kg</b> duly ISI marked conforming to <b>IS: 15683:2018</b> , with IS 4308, ISI marked ABC powder complete with squeeze grip release valve, discharge pipe locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: -30°C to + 60°C. <b>Brand LIFEGUARD</b>	8424/18%	4,875.00

### PREMIUM POWDER PORTABLE FIRE EXTINGUISHERS STORED PRESSURE TYPE (IS: 15683)

S. No.	LG- CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-121P	<b>PREMIUM Powder Fire Extinguisher (Stored Pressure type) Capacity 01 Kg</b> duly ISI marked conforming to <b>IS: 15683:2018</b> , with IS 4308, ISI marked ABC MAP 90% powder complete with squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: -30°C to + 60°C. <b>Brand LIFEGUARD</b>	8424/18%	2,000.00
2.	LG- 122P	<b>PREMIUM Powder Fire Extinguisher (Stored Pressure type) Capacity 02 Kg</b> duly ISI marked conforming to <b>IS: 15683:2018</b> , with IS 4308, ISI marked ABC MAP 90% powder complete with squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: -30°C to + 60°C. <b>Brand LIFEGUARD</b>	8424/18%	2,375.00
3.	LG-124P	<b>PREMIUM Powder Fire Extinguisher (Stored Pressure type) Capacity 04 Kg</b> duly ISI marked conforming to <b>IS: 15683:2018</b> , with IS 4308, ISI marked ABC MAP 90% powder complete with squeeze grip release valve, discharge pipe, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: -30°C to + 60°C. <b>Brand LIFEGUARD</b>	8424/18%	4,125.00
4.	LG-126P	<b>PREMIUM Powder Fire Extinguisher (Stored Pressure type) Capacity 06 Kg</b> duly ISI marked conforming to <b>IS: 15683:2018</b> , with IS 4308, ISI marked MAP 90% ABC powder complete with squeeze grip release valve, discharge pipe, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: -30°C to + 60°C. <b>Brand LIFEGUARD</b>	8424/18%	5,250.00
5.	LG-129P	<b>PREMIUM Powder Fire Extinguisher (Stored Pressure type) Capacity 09 Kg</b> duly ISI marked conforming to <b>IS: 15683:2018</b> , with IS 4308, ISI marked ABC MAP 90% powder complete with squeeze grip release valve, discharge pipe locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: -30°C to + 60°C. <b>Brand LIFEGUARD</b>	8424/18%	7,000.00

**POWDER PORTABLE FIRE EXTINGUISHERS GAS CARTRIDGE TYPE (IS: 15683)**

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-224	<b>Powder</b> Fire Extinguisher ( <b>Gas Cartridge type</b> ) Capacity <b>04 Kg</b> duly ISI marked conforming to <b>IS: 15683:2018</b> , with IS 4308, ISI marked ABC powder; Complete with <b>IS 4947</b> ISI marked Gas Cartridge with squeeze grip release valve, discharge pipe, locking arrangement, operation manual and bracket. Operating Temperature: -30°C to + 60°C. <b>Brand LIFEGUARD</b>	8424/18%	4,875.00
2.	LG-226	<b>Powder</b> Fire Extinguisher ( <b>Gas Cartridge type</b> ) Capacity <b>06 Kg</b> duly ISI marked conforming to <b>IS: 15683:2018</b> , with IS 4308, ISI marked ABC powder; Complete with <b>IS 4947</b> ISI marked Gas Cartridge with squeeze grip release valve, discharge pipe, locking arrangement, operation manual and bracket. Operating Temperature: -30°C to + 60°C. <b>Brand LIFEGUARD</b>	8424/18%	5,700.00
3.	LG-229	<b>Powder</b> Fire Extinguisher ( <b>Gas Cartridge type</b> ) Capacity <b>09 Kg</b> duly ISI marked conforming to <b>IS: 15683:2018</b> , with IS 4308, ISI marked ABC powder ; Complete with <b>IS 4947</b> ISI marked Gas Cartridge with squeeze grip release valve, discharge pipe locking arrangement, operation manual and bracket. Operating Temperature -30°C to + 60°C. <b>Brand LIFEGUARD</b>	8424/18%	6,875.00

**\*Also Available in ISI marked BC Powder IS: 4308, MAP 90% ISI marked ABC Powder or UL Listed MAP 90% ABC Powder.**

**POWDER WHEELED TYPE FIRE EXTINGUISHER (IS: 16018)**

S. No.	LG- CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-1225	<b>Powder Wheeled Fire Extinguisher Capacity 25 Kg Stored pressure type</b> duly ISI marked conforming to <b>IS: 16018</b> with rotary release valve, delivery hose, shut-off valve fitted with discharge nozzle & IS 4308, ISI marked BC Powder, Complete in all respect. Operating Temperature: - 30°C to + 55°C. <b>Brand LIFEGUARD</b>	8424/18%	16,000.00
2.	LG-2225	<b>Powder Wheeled Fire Extinguisher Capacity 25 Kg</b> duly ISI marked conforming to <b>IS: 16018</b> with G.M. Cap, delivery hose, shut-off valve fitted with discharge nozzle & <b>300 gm CO<sub>2</sub> gas cartridge</b> , IS 4308, ISI marked BC Powder, Complete in all respect. Operating Temperature: - 30°C to +55°C. <b>Brand LIFEGUARD</b>	8424/18%	15,250.00
3.	LG-3225	<b>Powder Wheeled Fire Extinguisher Capacity 25 Kg</b> duly ISI marked conforming to <b>IS: 16018</b> with G.M. Cap, delivery hose, shut-off valve fitted with discharge nozzle & <b>outer CO<sub>2</sub> cylinder</b> , IS 4308, ISI marked BC Powder, Complete in all respect. Operating Temperature: - 30°C to + 55°C. <b>Brand LIFEGUARD</b>	8424/18%	22,000.00
4.	LG-3250	<b>Powder Wheeled Fire Extinguisher Capacity 50 Kg</b> duly ISI marked conforming to <b>IS: 16018</b> with G.M. Cap, delivery hose, shut-off valve fitted with discharge nozzle & <b>outer CO<sub>2</sub> cylinder</b> , IS 4308, ISI marked BC Powder, Complete in all respect. Operating Temperature: - 30°C to + 55°C. <b>Brand LIFEGUARD</b>	8424/18%	31,250.00
5.	LG-3275	<b>Powder Wheeled Fire Extinguisher Capacity 75 Kg</b> duly ISI marked conforming to <b>IS: 16018</b> with G.M. Cap, delivery hose, shut-off valve fitted with discharge nozzle & <b>outer CO<sub>2</sub> cylinder</b> , IS 4308, ISI marked BC Powder, Complete in all respect. Operating Temperature: - 30°C to + 55°C. <b>Brand LIFEGUARD</b>	8424/18%	38,500.00

**\* Also Available in ABC Powder, IS: 4308**

**CO<sub>2</sub> PORTABLE FIRE EXTINGUISHERS (IS: 15683)**

S. No.	LG-CODE	DESCRIPTION	HSN CODE/ GST RATE	RATES (INR)
1.	LG-132	<b>CO<sub>2</sub> type</b> Fire Extinguisher ISI marked conforming to <b>IS: 15683. Capacity 2 Kg.</b> Complete with delivery hose horn, wheel type release valve, locking arrangement, operation manual and bracket. Operating Temperature: - 30°C to +60°C. <b>Brand LIFEGUARD</b>	8424/18%	7,500.00
2.	LG-133	<b>CO<sub>2</sub> type</b> Fire Extinguisher ISI marked conforming to <b>IS: 15683. Capacity 3 Kg.</b> Complete with delivery hose horn, wheel type release valve, locking arrangement, operation manual and bracket. Operating Temperature: - 30°C to + 60°C. <b>Brand LIFEGUARD</b>	8424/18%	9,000.00
3.	LG-134	<b>CO<sub>2</sub> type</b> Fire Extinguisher ISI marked conforming to <b>IS: 15683. Capacity 4.5 Kg.</b> Complete with delivery hose horn, wheel type release valve, locking arrangement, operation manual and bracket. Operating Temperature:- 30°C to +60°C. <b>Brand LIFEGUARD</b>	8424/18%	10,500.00

**CO<sub>2</sub> PORTABLE LIGHT WEIGHT ALUMINUM BODY FIRE EXTINGUISHERS (IS: 15683)**

S. No.	LG-CODE	DESCRIPTION	HSN CODE / GST RATE	RATES (INR)
1.	LG-132AL	<b>CO<sub>2</sub> type LIGHT WEIGHT ALUMINUM BODY</b> Fire Extinguisher ISI marked conforming to <b>IS: 15683. Capacity 2 Kg.</b> Complete with delivery hose horn, wheel type release valve, locking arrangement, operation manual and bracket. Operating Temperature: - 30°C to +60°C. <b>Brand LIFEGUARD</b>	8424/18%	9,500.00
2.	LG-134AL	<b>CO<sub>2</sub> type LIGHT WEIGHT ALUMINUM BODY</b> Fire Extinguisher ISI marked conforming to <b>IS: 15683. Capacity 4.5 Kg.</b> Complete with delivery hose horn, wheel type release valve, locking arrangement, operation manual and bracket. Operating Temperature:- 30°C to +60°C. <b>Brand LIFEGUARD</b>	8424/18%	15,500.00

**CO<sub>2</sub> WHEELED TYPE FIRE EXTINGUISHER (IS:16018)**

S. No.	LG- CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-336	<b>CO<sub>2</sub> Wheeled Fire Extinguisher</b> ISI marked conforming to <b>IS: 16018. Capacity 6.5 Kg.</b> Complete with composite trolley with handle & wheel, operation manual, wheel type release valve, locking arrangement and shut-off valve fitted with delivery hose horn. Operating Temperature: - 30°C to + 55°C. <b>Brand LIFEGUARD</b>	8424/18%	18,750.00
2.	LG-339	<b>CO<sub>2</sub> Wheeled Fire Extinguisher</b> ISI marked conforming to <b>IS: 16018. Capacity 9 Kg.</b> Complete with composite trolley with handle & wheel, operation manual, wheel type release valve, locking arrangement and shut-off valve fitted with delivery hose horn. Operating Temperature: -30°C to + 55°C. <b>Brand LIFEGUARD</b>	8424/18%	22,500.00
3.	LG-3322	<b>CO<sub>2</sub> Wheeled Fire Extinguisher</b> ISI marked conforming to <b>IS: 16018. Capacity 22.5 Kg.</b> Complete with composite trolley with handle & wheel, operation manual, wheel type release valve, locking arrangement and shut-off valve fitted with delivery hose horn. Operating Temperature: - 30°C to + 55°C. <b>Brand LIFEGUARD</b>	8424/18%	35,000.00
4.	LG-3345	<b>CO<sub>2</sub> Wheeled Fire Extinguisher. Capacity 45 Kg.</b> Complete with composite trolley with handle & wheel, operation manual, wheel type release valve, locking arrangement and shut-off valve fitted with delivery hose horn. Operating Temperature: - 30°C to + 55°C. <b>Brand LIFEGUARD</b>	8424/18%	67,500.00

**WATER PORTABLE FIRE EXTINGUISHERS (IS: 15683)**

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-106	<b>Water Fire Extinguisher Stored pressure</b> type ISI marked conforming to <b>IS: 15683. Capacity 6 litre.</b> Complete with delivery hose, squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: +5°C to + 60°C. <b>Brand LIFEGUARD</b>	8424/18%	2,625.00
2.	LG- 109	<b>Water Fire Extinguisher Stored pressure</b> type ISI marked conforming to <b>IS: 15683. Capacity 9 litre.</b> Complete with delivery hose, squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: +5°C to + 60°C. <b>Brand LIFEGUARD</b>	8424/18%	3,125.00
3.	LG-206	<b>Water Fire Extinguisher Gas Cartridge type</b> ISI marked conforming to <b>IS: 15683. Capacity 6 litre.</b> Complete with <b>IS: 4947</b> Gas Cartridge, delivery hose, squeeze grip release valve, locking arrangement, operation manual and bracket. Operating Temperature: +5°C to + 60°C. <b>Brand LIFEGUARD</b>	8424/18%	4,625.00
4.	LG-209	<b>Water Fire Extinguisher Gas Cartridge type</b> ISI marked conforming to <b>IS: 15683. Capacity 9 litre.</b> Complete with <b>IS: 4947</b> Gas Cartridge, delivery hose, squeeze grip release valve, locking arrangement, operation manual and bracket. Operating Temperature: +5°C to + 60°C. <b>Brand LIFEGUARD</b>	8424/18%	5,125.00

**WATER WHEELED TYPE FIRE EXTINGUISHERS (IS: 16018)**

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG- 1020	<b>Water Wheeled Fire Extinguisher</b> ISI marked conforming to <b>IS: 16018 Stored pressure type</b> with rotary release valve, delivery hose, shut-off valve fitted with discharge nozzle. Complete in all respect. Capacity <b>20 litre</b> . Operating Temperature: + 5°C to + 55°C <b>Brand LIFEGUARD</b>	8424/18%	14,500.00
2.	LG-2020	<b>Water Wheeled Fire Extinguisher</b> ISI marked conforming to <b>IS: 16018</b> with G.M. cap, delivery hose, shut-off valve fitted with discharge nozzle & <b>CO<sub>2</sub> gas cartridge</b> . Complete in all respect. Capacity <b>20 litre</b> . Operating Temperature: + 5°C to + 55°C <b>Brand LIFEGUARD</b>	8424/18%	13,000.00
3.	LG-2045	<b>Water Wheeled Fire Extinguisher</b> ISI marked conforming to <b>IS: 16018</b> with G.M. cap, delivery hose, shut-off valve fitted with discharge nozzle & <b>CO<sub>2</sub> gas cartridge</b> . Complete in all respect. Capacity <b>45 litre</b> . Operating Temperature: + 5°C to + 55°C <b>Brand LIFEGUARD</b>	8424/18%	17,000.00
4.	LG-2060	<b>Water Wheeled Fire Extinguisher</b> ISI marked conforming to <b>IS: 16018</b> with G.M. cap, delivery hose, shut-off valve fitted with discharge nozzle & <b>CO<sub>2</sub> gas cartridge</b> . Complete in all respect. Capacity <b>60 litre</b> . Operating Temperature: + 5°C to + 55°C <b>Brand LIFEGUARD</b>	8424/18%	18,000.00
5.	LG-3045	<b>Water Wheeled Fire Extinguisher</b> ISI marked conforming to <b>IS: 16018</b> with G.M. cap, delivery hose, shut-off valve fitted with discharge nozzle & <b>outer CO<sub>2</sub> Cylinder</b> . Complete in all respect. Capacity <b>45 litre</b> . Operating Temperature: + 5°C to + 55°C. <b>Brand LIFEGUARD</b>	8424/18%	23,500.00
6.	LG-3060	<b>Water Wheeled Fire Extinguisher</b> ISI marked conforming to <b>IS: 16018</b> with G.M. cap, delivery hose, shut-off valve fitted with discharge nozzle & <b>outer CO<sub>2</sub> Cylinder</b> . Complete in all respect. Capacity <b>60 litre</b> . Operating Temperature: + 5°C to + 55°C. <b>Brand LIFEGUARD</b>	8424/18%	25,000.00

**MECHANICAL FOAM (AFFF) PORTABLE FIRE EXTINGUISHERS (IS: 15683)**

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-116	<b>Mechanical Foam (AFFF)</b> Fire Extinguisher <b>Stored pressure</b> type ISI marked conforming to <b>IS: 15683</b> . Capacity <b>6 litre</b> . Complete with delivery hose, squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: +5°C to + 60°C. <b>Brand LIFEGUARD</b>	8424/18%	3,125.00
2.	LG- 119	<b>Mechanical Foam (AFFF)</b> Fire Extinguisher <b>Stored pressure</b> type ISI marked conforming to <b>IS: 15683</b> . Capacity <b>9 litre</b> . Complete with delivery hose, squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: +5°C to + 60°C. <b>Brand LIFEGUARD</b>	8424/18%	3,500.00
3.	LG-216	<b>Mechanical Foam (AFFF)</b> Fire Extinguisher <b>Gas Cartridge</b> type ISI marked conforming to <b>IS: 15683</b> . Capacity <b>6 litre</b> . Complete with gas cartridge, delivery hose, squeeze grip release valve, locking arrangement, operation manual and bracket. Operating Temperature: +5°C to + 60°C. <b>Brand LIFEGUARD</b>	8424/18%	5,000.00
4.	LG-219	<b>Mechanical Foam (AFFF)</b> Fire Extinguisher <b>Gas Cartridge</b> type ISI marked conforming to <b>IS: 15683</b> . Capacity <b>9 litre</b> . Complete with gas cartridge, delivery hose, squeeze grip release valve, locking arrangement, operation manual and bracket. Operating Temperature: +5°C to + 60°C. <b>Brand LIFEGUARD</b>	8424/18%	5,500.00

**MECHANICAL FOAM (AFFF) WHEELED TYPE FIRE EXTINGUISHERS (IS: 16018)**

S. No.	LG- CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-2120	<b>Mechanical Foam (AFFF) Wheeled Fire Extinguisher</b> ISI marked conforming to <b>IS:16018</b> with G.M. cap, delivery hose, shut-off valve fitted with discharge nozzle & <b>CO<sub>2</sub> gas cartridge</b> . Complete in all respect. Capacity <b>20 litre</b> . Operating Temperature: + 5°C to + 55°C <b>Brand LIFEGUARD</b>	8424/18%	13,750.00

2.	LG-2145	<b>Mechanical Foam (AFFF) Wheeled Fire Extinguisher ISI marked</b> conforming to <b>IS:16018</b> with G.M. cap, delivery hose, shut-off valve fitted with discharge nozzle & <b>CO<sub>2</sub> gas cartridge</b> . Complete in all respect. Capacity <b>45 litre</b> . Operating Temperature: + 5°C to + 55°C <b>Brand LIFEGUARD</b>	8424/18%	17,000.00
3.	LG-2160	<b>Mechanical Foam (AFFF) Wheeled Fire Extinguisher ISI marked</b> conforming to <b>IS:16018</b> with G.M. cap, delivery hose, shut-off valve fitted with discharge nozzle & <b>CO<sub>2</sub> gas cartridge</b> . Complete in all respect. Capacity <b>60 litre</b> . Operating Temperature: + 5°C to + 55°C <b>Brand LIFEGUARD</b>	8424/18%	18,000.00
4.	LG- 3145	<b>Mechanical Foam (AFFF) Wheeled Fire Extinguisher ISI marked</b> conforming to <b>IS:16018</b> with G.M. cap, delivery hose, shut-off valve with discharge nozzle & <b>outer CO<sub>2</sub> cylinder</b> . Complete in all respect. Capacity <b>45 litre</b> . Operating Temperature: + 5°C to + 55°C <b>Brand LIFEGUARD</b>	8424/18%	24,000.00
5.	LG- 3160	<b>Mechanical Foam (AFFF) Wheeled Fire Extinguisher ISI marked</b> conforming to <b>IS:16018</b> with G.M. cap, delivery hose, shut-off valve with discharge nozzle & <b>outer CO<sub>2</sub> cylinder</b> . Complete in all respect. Capacity <b>60 litre</b> . Operating Temperature: + 5°C to + 55°C <b>Brand LIFEGUARD</b>	8424/18%	25,500.00

#### WATER MIST TYPE FIRE EXTINGUISHERS

S. No.	LG- CODE	DESCRIPTION	HSN CODE/ GST RATE	RATES (INR)
1.	LG-164	<b>Water Mist Type Fire Extinguisher Stored pressure</b> type ISI marked conforming to <b>IS: 15683</b> . Capacity <b>4 litre</b> . Complete with delivery hose fitted with mist forming nozzle, squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: +5°C to + 60°C. <b>Brand LIFEGUARD</b>	8424/18%	8,500.00
2.	LG-166	<b>Water Mist Type Fire Extinguisher Stored pressure</b> type ISI marked conforming to <b>IS: 15683</b> . Capacity <b>6 litre</b> . Complete with delivery hose fitted with mist forming nozzle, squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: +5°C to + 60°C. <b>Brand LIFEGUARD</b>	8424/18%	9,625.00
3.	LG-169	<b>Water Mist Type Fire Extinguisher Stored pressure</b> type ISI marked conforming to <b>IS: 15683</b> . Capacity <b>9 litre</b> . Complete with delivery hose fitted with mist forming nozzle, squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: +5°C to + 60°C. <b>Brand LIFEGUARD</b>	8424/18%	11,250.00
4.	LG-3609	<b>Water Mist System &amp; CAFS (COMPRESSED AIR FOAM SYSTEM) Backpack type Fire Extinguisher</b> with aerodynamics technology from flow engineering applications involving liquid and gas mixtures, <b>Capacity 9 Litre</b> . Complete with delivery hose, extinguishing gun, User Manual and propellant gas cylinder filled with 2litres of compressed air. Operating Temperature: ±5°C to +60°C. <b>Brand LIFEGUARD</b>	8424/18%	4,50,000.00
5.	LG-3615	<b>Water Mist System &amp; CAFS (COMPRESSED AIR FOAM SYSTEM) Backpack type Fire Extinguisher</b> with aerodynamics technology from flow engineering applications involving liquid and gas mixtures with an option of usage along with a breathing apparatus, <b>Capacity 15 Litre</b> . Complete with delivery hose, extinguishing gun, User Manual and propellant gas cylinder filled with 2litres of compressed air. Operating Temperature: ±5°C to +60°C. <b>Brand LIFEGUARD</b>	8424/18%	6,12,500.00
6.	LG-3645	<b>WHEELED TYPE Water Mist System &amp; CAFS (COMPRESSED AIR FOAM SYSTEM) Fire Extinguisher ISI marked IS: 16018</b> with aerodynamics technology from flow engineering applications involving liquid and gas mixtures with the combination of the highly sophisticated Guns and a trolley supply system <b>Capacity 45 Litre</b> . Complete with delivery hose, extinguishing gun, User Manual and propellant gas cylinder filled with 6.8litres of compressed air. Operating Temperature: - +5°C to +60°C. <b>Brand LIFEGUARD</b>	8424/18%	7,25,000.00

#### CLEAN AGENT TYPE FIRE EXTINGUISHERS (ECO FRIENDLY) (IS: 15683)

S. No.	LG- CODE	DESCRIPTION	HSN CODE/ GST RATE	RATES (INR)
1.	LG-141	<b>Clean Agent (Stored Pressure) Type Capacity 1 Kg Fire Extinguisher</b> filled with HFC 236FAClean Agent Gas. Complete with squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Complete in all respect. <b>Brand LIFEGUARD</b>	8424/18%	7,125.00

2.	LG-142	<b>Clean Agent (Stored Pressure) Type Capacity 2 Kg Fire Extinguisher ISI marked IS: 15683</b> filled with HFC 236FAClean Agent Gas. Complete with squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Complete in all respect. Operating Temperature: -30°C to + 60°C. <b>Brand LIFEGUARD</b>	8424/18%	13,750.00
3.	LG-144	<b>Clean Agent (Stored Pressure) Type Capacity 4 Kg Fire Extinguisher ISI marked IS: 15683</b> filled with HFC 236FAClean Agent Gas. Complete with squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Complete in all respect. Operating Temperature: -30°C to + 60°C. <b>Brand LIFEGUARD</b>	8424/18%	26,000.00
4.	LG-146	<b>Clean Agent (Stored Pressure) Type Capacity 6 Kg Fire Extinguisher ISI marked IS: 15683</b> filled with HFC 236FAClean Agent Gas. Complete with squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Complete in all respect. Operating Temperature: -30°C to + 60°C. <b>Brand LIFEGUARD</b>	8424/18%	35,000.00

**WET CHEMICAL (KITCHEN) 'F' TYPE FIRE EXTINGUISHER**

S. No.	LG- CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG- 154	<b>Wet Chemical (Stored Pressure) "F" Type ISI marked IS: 15683 Capacity 4 litre</b> Fire Extinguisher. Complete with <b>SS body</b> , squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Complete in all respect <b>for Kitchen Fire. Brand LIFEGUARD</b>	8424/18%	12,000.00
2.	LG-156	<b>Wet Chemical (Stored Pressure) "F" Type ISI marked IS: 15683 Capacity 6 litre</b> Fire Extinguisher. Complete with <b>SS body</b> , squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Complete in all respect <b>for Kitchen Fire. Brand LIFEGUARD</b>	8424/18%	14,000.00
3.	LG-159	<b>Wet Chemical (Stored Pressure) "F" Type ISI marked IS: 15683 Capacity 9 litre</b> Fire Extinguisher. Complete with <b>SS body</b> , squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Complete in all respect <b>for Kitchen Fire. Brand LIFEGUARD</b>	8424/18%	17,500.00

**CLEAN AGENT MODULAR TYPE FIRE EXTINGUISHERS CE CERTIFIED**

S. No.	LG- CODE	DESCRIPTION	HSN CODE/ GST RATE	RATES (INR)
1.	LG-1702	<b>Clean Agent Modular</b> (ceiling mounted) Type Capacity <b>2 Kg</b> CE certified Fire Extinguisher filled with HFC 236FAClean Agent Gas. Complete in all respect. <b>Brand LIFEGUARD</b>	8424/18%	13,750.00
2.	LG-1705	<b>Clean Agent Modular</b> (ceiling mounted) Type Capacity <b>5 Kg</b> CE certified Fire Extinguisher filled with HFC 236FAClean Agent Gas. Complete in all respect. <b>Brand LIFEGUARD</b>	8424/18%	30,000.00
3.	LG-1710	<b>Clean Agent Modular</b> (ceiling mounted) Type Capacity <b>10 Kg</b> CE certified Fire Extinguisher filled with HFC 236FAClean Agent Gas. Complete in all respect. <b>Brand LIFEGUARD</b>	8424/18%	52,500.00
4.	LG-1715	<b>Clean Agent Modular</b> (ceiling mounted) Type Capacity <b>15 Kg</b> CE certified Fire Extinguisher filled with HFC 236FAClean Agent Gas. Complete in all respect. <b>Brand LIFEGUARD</b>	8424/18%	85,000.00

**ABC MODULAR TYPE FIRE EXTINGUISHERS CE CERTIFIED**

S. No.	LG- CODE	DESCRIPTION	HSN CODE/ GST RATE	RATES (INR)
1.	LG-1602	<b>ABC Modular</b> Type <b>CE certified</b> Capacity <b>2 Kg</b> Fire Extinguisher filled with ISI marked IS: 4308 ABC Powder. Complete in all respect. <b>Brand LIFEGUARD</b>	8424/18%	2,750.00
2.	LG-1605	<b>ABC Modular</b> Type <b>CE certified</b> Capacity <b>5 Kg</b> Fire Extinguisher filled with ISI marked IS: 4308 ABC Powder. Complete in all respect. <b>Brand LIFEGUARD</b>	8424/18%	4,250.00
3.	LG-1610	<b>ABC Modular</b> Type <b>CE certified</b> Capacity <b>10 Kg</b> Fire Extinguisher filled with ISI marked IS: 4308 ABC Powder. Complete in all respect. <b>Brand LIFEGUARD</b>	8424/18%	5,875.00
4.	LG-1615	<b>ABC Modular</b> Type <b>CE certified</b> Capacity <b>15 Kg</b> Fire Extinguisher filled with ISI marked IS: 4308 ABC Powder. Complete in all respect. <b>Brand LIFEGUARD</b>	8424/18%	8,750.00

\* Also available in UL Listed MAP90% ABC powder.

**D Class POWDER PORTABLE FIRE EXTINGUISHERS**

S. No.	LG- CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-126D	<b>Powder</b> Fire Extinguisher ( <b>Stored Pressure type</b> ) Capacity <b>06 Kg</b> D Class powder for Metal Fire complete with specially designed applicator nozzle, squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. <b>Brand LIFEGUARD</b>	8424/18%	12,000.00
2.	LG- 129D	<b>Powder</b> Fire Extinguisher ( <b>Stored Pressure type</b> ) Capacity <b>09 Kg</b> D Class powder for Metal Fire complete with specially designed applicator nozzle, squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. <b>Brand LIFEGUARD</b>	8424/18%	15,750.00

**LANDING VALVES/ HYDRANT VALVES (IS: 5290)**

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-401	<b>Gun Metal</b> Landing Valve <b>Single Head</b> dia. 63 mm ( <b>Type A</b> ) ISI marked IS: 5290 with 1 no. ABS Blank Cap complete in all respect <b>Brand LIFEGUARD</b>	7412/18%	15,000.00
2.	LG-402	<b>Stainless Steel</b> Landing Valve <b>Single Head</b> dia. 63 mm ( <b>Type A</b> ) ISI marked IS: 5290 with 1 no. ABS Blank Cap complete in all respect <b>Brand LIFEGUARD</b>	7307/18%	9,500.00
3.	LG-406	<b>Gun Metal</b> Landing Valve <b>Double Head</b> dia. 63 mm ( <b>Type B</b> ) ISI marked IS: 5290 with 2 no. ABS Blank Caps complete in all respect <b>Brand LIFEGUARD</b>	7412/18%	38,750.00
4.	LG-407	<b>Stainless Steel</b> Landing Valve <b>Double Head</b> dia. 63 mm ( <b>Type B</b> ) ISI marked IS: 5290 with 2 no. ABS Blank Caps complete in all respect <b>Brand LIFEGUARD</b>	7307/18%	19,500.00

**FIRE HOSE DELIVERY COUPLING, BRANCH PIPE AND NOZZLE (IS: 903)**

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-411	<b>Gun Metal</b> Branch Pipe dia.63 mm & nozzle 20 mm ISI marked IS 903 complete in all respect <b>Brand LIFEGUARD</b>	7412/18%	5,625.00
2.	LG-412	<b>Stainless Steel</b> Branch Pipe dia.63 mm & nozzle 20 mm ISI marked IS 903 complete in all respect <b>Brand LIFEGUARD</b>	7307/18%	3,125.00
3.	LG-413	<b>Aluminum Alloy</b> Branch Pipe dia.63 mm & nozzle 20 mm ISI marked IS 903 complete in all respect <b>Brand LIFEGUARD</b>	7609/18%	1,850.00
4.	LG-416	<b>Gun Metal</b> Fire Hose Delivery Coupling (MALE/ FEMALE) dia. 63 mm ISI marked IS 903 complete in all respect <b>Brand LIFEGUARD</b>	7412/18%	6,250.00
5.	LG-417	<b>Stainless Steel</b> Fire Hose Delivery Coupling (MALE/FEMALE) dia. 63 mm ISI marked IS 903 complete in all respect <b>Brand LIFEGUARD</b>	7307/18%	3,500.00
6.	LG-418	<b>Aluminum Alloy</b> Fire Hose Delivery Coupling (MALE/FEMALE) dia. 63 mm ISI marked IS 903 complete in all respect <b>Brand LIFEGUARD</b>	7609/18%	2,000.00

**FIRE HOSE BOXES**

S. No.	LG- CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-501A	Hose box (Single Door) (500mm x 500mm x 250mm) 18 gauge suitable for 1 no. 15mtr. Hose and 1 no short branch pipe. Complete in all respect <b>Brand LIFEGUARD</b>	7310/18%	4,500.00
2.	LG-501G	Hose box (Double Door) (750mm x 600mm x 250mm) 18 gauge suitable for 2 no. 15mtr. Hose and 1 no short branch pipe. Complete in all respect <b>Brand LIFEGUARD</b>	7310/18%	6,000.00
3.	LG-501C	Hose box (Double Door) (750mm x 600mm x 250mm) 16 gauge suitable for 2 no. 15mtr. Hose and 1 no short branch pipe. Complete in all respect <b>Brand LIFEGUARD</b>	7310/18%	7,250.00
4.	LG-501D	Hose box (Double Door) (900mm x 600mm x 500mm) 16 gauge suitable for 2 no. 15mtr. Hose and 1 no short branch pipe and 1 no hydrant. Complete in all respect <b>Brand LIFEGUARD</b>	7310/18%	15,000.00
5.	LG-501H	Hose box (Double Door) (900mm x 600mm x 500mm) 18 gauge suitable for 2 no. 15mtr. Hose and 1 no short branch pipe and 1 no hydrant. Complete in all respect <b>Brand LIFEGUARD</b>	7310/18%	12,750.00

6.	LG-501E	Fire hose cabinet door (40mm x 40mm x 5mm) angle depth fabricated with 2100mm x 1200mm MS sheet. Complete in all respect <b>Brand LIFEGUARD</b>	7310/18%	20,000.00
7.	LG-501F	Fire hose cabinet door (40mm x 40mm x 5mm) angle depth fabricated with 2100mm x 900mm MS sheet. Complete in all respect <b>Brand LIFEGUARD</b>	7310/18%	18,000.00

**FIRST AID HOSE REEL (IS: 884)**

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-421	Manual Swing type fire hose reel ISI marked IS: 884 with Thermoplastic hose pipe 30mtr. Long, dia 20mm, ISI marked IS: 12585 with GM shut off nozzle complete in all respect Type II (W.P. 10.2 Kgf/cm <sup>2</sup> ). <b>Brand LIFEGUARD</b>	8424/18%	11,750.00
2.	LG-421A	Shut-Off Nozzle (Gun Metal) for Hose Reel. <b>Brand LIFEGUARD</b>	7412/18%	1000.00
3.	LG-421B	Hose pipe 30mtr. Long, dia 20mm ISI marked <b>Brand LIFEGUARD</b> 1. Thermoplastic hose pipe Type I (W.P. 7.2 Kgf/cm <sup>2</sup> ) IS : 12585 2. Thermoplastic hose pipe Type II (W.P. 10.2 Kgf/cm <sup>2</sup> ) IS : 12585 3. Rubber hose pipe Type II (W.P. 10.2 Kgf/cm <sup>2</sup> ) IS : 444	3917/18% 3917/18% 4009/18%	3,750.00 4,125.00 4,750.00
4.	LG-421C	Manual Swing type fire Hose Reel Drum ISI marked IS:884 <b>Brand LIFEGUARD.</b>	8424/18%	6,750.00
5.	LG-421D	Compact Hose Reel Imported type with company fitted accessories, complete in all respect. <b>Brand LIFEGUARD</b>	8424/18%	11,500.00

**FIRE HOSES FOR HYDRANT SYSTEM**

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-422A	<b>Reinforced Rubber Lined (RRL) Fire Hose</b> Type 1 <b>ISI marked</b> conforming to IS: 636, <b>15mtr</b> long with <b>ISI marked Gun Metal</b> Coupling dia 63 mm with GI Binding. <b>Brand LIFEGUARD</b>	5909/12%	10,000.00
2.	LG-422I	<b>Reinforced Rubber Lined (RRL) Fire Hose</b> Type 2 <b>ISI marked</b> conforming to IS: 636, <b>15mtr</b> long with <b>ISI marked Gun Metal</b> Coupling dia 63 mm with GI Binding. <b>Brand LIFEGUARD</b>	5909/12%	10,500.00
3.	LG-422B	<b>Reinforced Rubber Lined (RRL) Fire Hose</b> Type 3 <b>ISI marked</b> conforming to IS: 636, <b>15mtr</b> long with <b>ISI marked Gun Metal</b> Coupling dia 63 mm with GI Binding. <b>Brand LIFEGUARD</b>	5909/12%	15,000.00
4.	LG-422C	<b>Reinforced Rubber Lined (RRL) Fire Hose</b> Type 1 <b>ISI marked</b> conforming to IS: 636, <b>15mtr</b> long with <b>ISI marked Stainless Steel</b> Coupling dia 63 mm with GI Binding. <b>Brand LIFEGUARD</b>	5909/12%	8,000.00
5.	LG-422 J	<b>Reinforced Rubber Lined (RRL) Fire Hose</b> Type 2 <b>ISI marked</b> conforming to IS: 636, <b>15mtr</b> long with <b>ISI marked Stainless Steel</b> Coupling dia 63 mm with GI Binding. <b>Brand LIFEGUARD</b>	5909/12%	8,375.00
6.	LG-422D	<b>Reinforced Rubber Lined (RRL) Fire Hose</b> Type 3 <b>ISI marked</b> conforming to IS: 636, <b>15mtr</b> long with <b>ISI marked Stainless Steel</b> Coupling dia 63 mm with GI Binding. <b>Brand LIFEGUARD</b>	5909/12%	13,500.00
7.	LG-422E	<b>Reinforced Rubber Lined (RRL) Fire Hose</b> Type 1 <b>ISI marked</b> conforming to IS: 636, <b>30mtr</b> long with <b>ISI marked Gun Metal</b> Coupling dia 63 mm with GI Binding. <b>Brand LIFEGUARD</b>	5909/12%	16,000.00
8.	LG-422F	<b>Reinforced Rubber Lined (RRL) Fire Hose</b> Type 1 <b>ISI marked</b> conforming to IS: 636, <b>30mtr</b> long with <b>ISI marked Stainless Steel</b> Coupling dia 63 mm with GI Binding. <b>Brand LIFEGUARD</b>	5909/12%	13,500.00
9.	LG-422G	<b>Controlled Percolating (CP) Fire Hose</b> <b>ISI marked</b> conforming to IS: 8423, <b>15mtr</b> long with <b>ISI marked Gun Metal</b> Coupling dia 63 mm with GI Binding. <b>Brand LIFEGUARD</b>	5909/12%	9,375.00
10.	LG-422H	<b>Controlled Percolating (CP) Fire Hose</b> <b>ISI marked</b> conforming to IS: 8423, <b>15mtr</b> long with <b>ISI marked Stainless Steel</b> Coupling dia 63 mm. <b>Brand LIFEGUARD</b>	5909/12%	7,750.00

**WATER / FOAM MONITORS**

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-526 0063	<b>Water Monitor 63mm dia</b> to be operated in pressure line with 7-12 Kg/cm <sup>2</sup> , Inlet Flange NB 75 mm. Flow of <b>1750lpm</b> with throw range of up to <b>52Mtrs</b> at angle of 30°c. <b>Brand LIFEGUARD</b>	8424/18%	30,000.00
2.	LG-526 0075	<b>Water Monitor 75mm dia</b> to be operated in pressure line with 7-12 Kg/cm <sup>2</sup> , Inlet Flange NB 100 mm. Flow of <b>2580lpm</b> with throw range of up to <b>62Mtrs</b> at angle of 30°c. <b>Brand LIFEGUARD</b>	8424/18%	40,000.00
3.	LG-526 0100	<b>Water Monitor 100mm dia</b> to be operated in pressure line with 7-12 Kg/cm <sup>2</sup> , Inlet Flange NB 150 mm. Flow of <b>3750lpm</b> (with manual) throw range up to <b>67Mtrs</b> at angle of 30°c. <b>Brand LIFEGUARD</b>	8424/18%	67,500.00
4.	LG-526 1063	<b>Foam Monitor 63mm dia</b> to be operated in pressure line with 7-12 Kg/cm <sup>2</sup> , Inlet Flange NB 75 mm with <b>FB 5X</b> Nozzle. <b>Brand LIFEGUARD</b>	8424/18%	50,000.00
5.	LG-526 1075	<b>Foam Monitor 75mm dia</b> to be operated in pressure line with 7-12 Kg/cm <sup>2</sup> , Inlet Flange NB 100 mm with Aqua Nozzle. <b>Brand LIFEGUARD</b>	8424/18%	1,70,000.00

**FIRE BRIGADE CONNECTION**

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-423B	Two way Fire brigade connection dia 63mm. complete in all respect. <b>Brand LIFEGUARD</b>	7412/18%	8,500.00
2.	LG-423C	Three way Fire brigade connection dia 63mm. complete in all respect. <b>Brand LIFEGUARD</b>	7412/18%	11,000.00
3.	LG-423A	Four way Fire brigade connection dia 63mm. complete in all respect. <b>Brand LIFEGUARD</b>	7412/18%	16,500.00
4.	LG-502	Draw out connection. complete in all respect. <b>Brand LIFEGUARD</b>	7412/18%	7,500.00
5.	LG-517	Air Release Valve. <b>Brand LIFEGUARD</b>	7412/18%	2,250.00

**AUTOMATIC SPRINKLERS**

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-503B	Pendent type automatic sprinkler (ISI MARKED) (LIFEGUARD)	8424/12%	292.50
2.	LG-503D	Upright type automatic sprinkler (ISI MARKED) (LIFEGUARD)	8424/12%	292.50
3.	LG-503F	Side wall type automatic sprinkler (ISI MARKED) (LIFEGUARD)	8424/12%	325.00
4.	LG-503A	Pendent type automatic sprinkler (UL Listed)	8424/12%	410.00
5.	LG-503C	Upright type automatic sprinkler (UL Listed)	8424/12%	410.00
6.	LG-503E	Side wall type automatic sprinkler (UL Listed)	8424/12%	475.00
7.	LG-503G	Concealed type automatic sprinkler (UL Listed)	8424/12%	1,925.00
8.	LG-541	Water Curtain Nozzle (15 mm)	8424/18%	700.00
9.	LG-541	Water Curtain Nozzle (25 mm)	8424/18%	950.00
10.	-----	Fire Alarm valve UL Listed (100 mm diameter) complete	8481/18%	73,750.00

**FIRE DETECTION SYSTEMS & ACCESSORIES**

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-521 SD	Smoke Detector with 360° identification in alarm condition.	8531/18%	1,775.00
2.	LG-521 RD	Heat Detector CUM ROR with 360° identification in alarm condition.	8531/18%	1,925.00
3.	LG-521 HD	Heat Detector with 360° identification in alarm condition.	8531/18%	1,837.50
4.	LG-521 MD	Multi-criteria Detector with 360° identification in alarm condition.	8531/18%	1,900.00
5.	LG-545 II	2-Zone Fire Alarm Control Panel Complies to IS 2189:1999 and Tested by ERTL (N), 2 x 16 character backlit LCD display, NO/NC contacts for both fire and fault. <b>Brand LIFEGUARD</b>	8531/18%	8,625.00
6.	LG-545 IV	4-Zone Fire Alarm Control Panel Complies to IS 2189:1999 and Tested by ERTL (N), 2 x 16 character backlit LCD display, NO/NC contacts for both fire and fault. <b>Brand LIFEGUARD</b>	8531/18%	11,200.00
7.	LG-545 VI	6-Zone Fire Alarm Control Panel Complies to IS 2189:1999 and Tested by ERTL (N), 2 x 16 character backlit LCD display, NO/NC contacts for both fire and fault. <b>Brand LIFEGUARD</b>	8531/18%	16,950.00

8.	LG-545 VIII	8-Zone Fire Alarm Control Panel Complies to IS 2189:1999 and Tested by ERTL (N), 2 x 16 character backlit LCD display, NO/NC contacts for both fire and fault. <b>Brand LIFEGUARD</b>	8531/18%	19,975.00
9.	LG-545 X	10-Zone Fire Alarm Control Panel Complies to IS 2189:1999 and Tested by ERTL (N), 2 x 16 character backlit LCD display, NO/NC contacts for both fire and fault. <b>Brand LIFEGUARD</b>	8531/18%	22,425.00
10.	LG-520A	Manual call Point (MCP) ABS. <b>Brand LIFEGUARD</b>	8531/18%	575.00
11.	LG-520B	Hooter (MS) 24 Volt ABS. <b>Brand LIFEGUARD</b>	8531/18%	725.00
12.	LG-520C	Response Indicator ABS. <b>Brand LIFEGUARD</b>	8531/18%	205.00

**TOTAL GAS FLOODING PANEL**

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-546 II	<b>2-Zone Total Gas Flooding Panel</b> Complies to IS 2189:1999 and Tested by ERTL (N), 2 x 16 character backlit LCD display, NO/NC contacts for both fire and fault. <b>Brand LIFEGUARD</b>	8531/18%	16,525.00
2.	LG-546 IV	<b>4-Zone Total Gas Flooding Panel</b> Complies to IS 2189:1999 and Tested by ERTL (N), 2 x 16 character backlit LCD display, NO/NC contacts for both fire and fault. <b>Brand LIFEGUARD</b>	8531/18%	30,000.00

**WEIGHT SURVEILLANCE MODULE (CO<sub>2</sub>, FM-200, NOVEC etc.)**

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG - 611A	<b>Weight Surveillance Module Max Wt. 200 KG</b> , with collar and necessary cables. <b>Brand LIFEGUARD</b>	8423/18%	19,625.00
2.	LG - 611B	<b>Weight Surveillance Module Max Wt. 500 KG</b> , with collar and necessary cables. <b>Brand LIFEGUARD</b>	8423/18%	20,375.00
3.	LG - 611C	<b>Weight Surveillance Module Max Wt. 200 KG</b> , with platform, collar and necessary cables. <b>Brand LIFEGUARD</b>	8423/18%	20,125.00
4.	LG - 611D	<b>Weight Surveillance Module Max Wt. 500 KG</b> , with platform, collar and necessary cables. <b>Brand LIFEGUARD</b>	8423/18%	20,750.00

**ACTOK LIFEGUARD STICKER & CORD**

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG - 560	Supply of <b>Fire Suppression Sticker with composite material</b> being a mixture of microcapsules with a heating compound. <b>Operating Temperature 150 °C</b> , Ambient Temperature from -50 °C to +80 °C. Warranty period 5 years & ISO 9000:2011, ISO 9001:2015, en Approval WBO/8/I/CNBOP-PIB 2015 Edition 2 (Europe), Test Certificate from competent authority etc. Ambient/ Operating Temperatures:-50 °C to +80 °C. Shelf Life: 60 Months from the date of Issue Protection Class: IP20, <b>Capacity: 0.2 Units</b>	8424/18%	2,062.50
2.	LG - 56015	Supply of <b>Fire Suppression Sticker with composite material</b> being a mixture of microcapsules with a heating compound. <b>Operating Temperature 150 °C</b> , Ambient Temperature from -50 °C to +80 °C. Warranty period 5 years & ISO 9000:2011, ISO 9001:2015, en Approval WBO/8/I/CNBOP-PIB 2015 Edition 2 (Europe), Test Certificate from competent authority etc. Ambient/ Operating Temperatures:-50 °C to +80 °C. Shelf Life: 60 Months from the date of Issue Protection Class: IP20, <b>Capacity: 15 Units</b>	8424/18%	11,750.00
3.	LG - 56025	Supply of <b>Fire Suppression Sticker with composite material</b> being a mixture of microcapsules with a heating compound. <b>Operating Temperature 150 °C</b> , Ambient Temperature from -50 °C to +80 °C. Warranty period 5 years & ISO 9000:2011, ISO 9001:2015, en Approval WBO/8/I/CNBOP-PIB 2015 Edition 2 (Europe), Test Certificate from competent authority etc. Ambient/ Operating Temperatures:-50 °C to +80 °C. Shelf Life: 60 Months from the date of Issue Protection Class: IP20, <b>Capacity: 25 Units</b>	8424/18%	17,250.00
4.	LG - 56045	Supply of <b>Fire Suppression Sticker with composite material</b> being a mixture of microcapsules with a heating compound. <b>Operating Temperature 150 °C</b> , Ambient Temperature from -50 °C to +80 °C. Warranty period 5 years & ISO 9000:2011, ISO 9001:2015, en Approval WBO/8/I/CNBOP-PIB 2015 Edition 2 (Europe), Test Certificate from competent authority etc. Ambient/ Operating Temperatures:-50 °C to +80 °C. Shelf Life: 60 Months from the date of Issue Protection Class: IP20, <b>Capacity: 45 Units</b>	8424/18%	23,750.00
5.	LG - 56065	Supply of <b>Fire Suppression Sticker with composite material</b> being a mixture of microcapsules with a heating compound. <b>Operating Temperature 150 °C</b> , Ambient Temperature from -50 °C to +80 °C. Warranty period 5 years & ISO 9000:2011, ISO 9001:2015, en Approval WBO/8/I/CNBOP-PIB 2015 Edition 2 (Europe), Test Certificate from competent authority etc. Ambient/ Operating Temperatures:-50 °C to +80 °C. Shelf Life: 60 Months from the date of Issue Protection Class: IP20, <b>Capacity: 65 Units</b>	8424/18%	37,500.00

6.	LG - 561	<b>Digital Linear Heat Detector Cord with composite material</b> being a mixture of microcapsules with a heating compound. <b>Operating Temperature 150°C</b> , Ambient Temperature from -50°C to +80°C. Warranty period 5 years & ISO 9000:2011, ISO 9001:2015, en Approval WBO/8/I/CNBOP-PIB 2015 Edition 2 (Europe), Test Certificate from competent authority etc. Ambient/ Operating Temperatures:-50°C to +80°C. Shelf Life: 60 Months from the date of Issue. Complete with all necessary installation accessories (cable & insulations) for protection cover of connecting teeth.	8424/18%	24,750.00
----	----------	---	----------	-----------

#### EMERGENCY LIGHTS

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG - 641	<b>EMERGENCY LIGHT</b> providing through 16Watt <b>Twin UL Listed High Intensity LED</b> fitted Lamps with <b>Adjustable Swivel Type Beam Lights</b> fitted upon Powder Coated CRCA/MS Sheet Sleek Electronic Cabinet with Customized <b>Signage</b> fitted with 12V, 7AH SMF Battery giving <b>Battery Backup of Upto 5 Hours</b> provided with feature of <b>Trickle Charging</b> facilitating Overcharging and Low Battery Protection. 4 nos. <b>UL certified</b> Dual Tone LEDs with CRI Index greater than 90 provide maximum Smoke Penetration from each Lamp. Certificate of UL listed LED used are provided with each unit of Emergency Light. Electrical Supply is suitable for 230V 50Hz AC fitted with <b>Fuse safety. Brand LIFEGUARD</b>	8513/18%	6,250.00
2.	LG - 642	<b>EGRESS EDGELIT LIGHT</b> with customizable print and color, with backup of 2-3 hours on battery. <b>Brand LIFEGUARD</b> Single Side (per sq. inch.) Red/Green LED Double Side (per sq. inch.) Red/Green LED	8513/18%	53.75 68.75
3.	LG - 642A	<b>EGRESS EDGELIT LIGHT</b> with customizable print and color, without battery backup. <b>Brand LIFEGUARD</b> Single Side (per sq. inch.) Red/Green LED Double Side (per sq. inch.) Red/Green LED	8531/18%	47.50 62.50
4.	LG-528	<b>Photoluminescence Emergency Glow</b> signage, as per specification. <b>Brand LIFEGUARD</b> 1. With aluminum Base (per. Sq. inch) Single Side 2. With aluminum Base (per. Sq. inch) Double Side 3. With Acrylic Base (per. Sq. inch) Single Side 4. With aluminum Base (per. Sq. inch) Double Side	8310/18%	20.00 40.00 18.75 37.50

#### ALGORITHMIC ADDRESSABLE FIRE DETECTION SYSTEM

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-CLOYN02 BING	The <b>C-LYON Algorithmic Control Panel</b> is EN 54-2 and EN 54-4 according to the latest CE Directives/Regulation. Configurable with 2 loops. Loop Capability 99 points. Capacity of 4095 events with date and time. Backlit LCD display with 4 lines and 40 characters. Configurable with the PC-EASY Co-NET software. Allows connections of up to 8 repeaters and/or 8 control panels on network.	8531/18%	1,01,625.00
2.	LG-ZAFIRO 2 BING	The <b>ZAFIR Algorithmic Control Panel</b> is EN 54-2 and EN 54-4 according to the latest CE Directives/Regulation. Configurable with 2 loops. Loop Capability 199 points. Capacity of 4095 events with date and time. Backlit LCD display with 4 lines and 40 characters. Configurable with the PC-EASY Co-NET software. Allows connections of up to 8 repeaters and/or 8 control panels on network.	8531/18%	1,56,500.00
3.	LG-LYONING	The <b>LYON Algorithmic Control Panel</b> is EN 54-2 and EN 54-4 according to the latest CE Directives/Regulation. Configurable with 4 loops and expandable up to 20 loops Loop Capability 199 points. Capacity of 4095 events with date and time. Backlit LCD display with 4 lines and 40 characters. Configurable with the PC-EASY Co-NET software. Allows connections of up to 8 repeaters and/or 8 control panels on network.	8531/18%	2,24,700.00
4.	LG-ZYR	<b>Repeater Panel</b> for LYON, C.LYON and ZAFIR Connect up to 15 repeaters No supply required up to 3 repeaters	8531/18%	1,26,875.00
5.	LG- A30XTA	Algorithmic <b>Addressable Heat Sensor</b> for fire detection. The <b>A30XTA</b> is capable of registering absolute temperatures (heat sensor) but also temperature rise ( <b>ROR</b> ). Two red LED in alarm condition. Identification from any direction (360°). Easy connection, without polarity.	8531/18%	4,800.00
6.	LG-A3XHAS	Algorithmic <b>Addressable Smoke Sensor</b> for fire detection. The sensor <b>A30XHAS</b> has an optical smoke sensor. Two Red LED in alarm condition. Identification from any direction (360°).	8531/18%	4,875.00

7.	LG-A30XHA	Algorithmic <b>Addressable Multi-criteria Sensor</b> for fire detection. The sensor <b>A30XHA</b> has an optical smoke sensor and also has a static heat element that sets it into alarm status when temperature reaches 55° C. Two Red LED in alarm condition. Identification from any direction (360°).	8531/18%	5,200.00
8.	LG- PUCAY	Resettable <b>Manual Call Point</b> (with short-circuit isolator) for algorithmic addressable detection systems. Easily resettable call point by pushing yellow button on the front side. Transparent protector cover to avoid accidental false alarms.	8531/18%	4,375.00
9.	LG- MSTAY	<b>Monitor Module-</b> Microprocessor based algorithmic addressable device (with short-circuit isolator) installed as another element inside the loop. The Master Detection Module is placed in a rectangular, heat-resistant ABS box.	8531/18%	6,125.00
10.	LG- MDA1Y	<b>Relay Module-</b> Microprocessor based algorithmic addressable device (with short-circuit isolator) installed as another element inside the loop. The device is placed in a rectangular heat-resistant ABS box.	8531/18%	8,562.50
11.	LG- MDA2Y	<b>Relay Module(II)-</b> Microprocessor based algorithmic addressable device (with short-circuit isolator) installed as another element inside the loop. The device is placed in a rectangular heat-resistant ABS box.	8531/18%	9,312.50
12.	LG-KMAY	<b>Supervision Module</b> Microprocessor based algorithmic addressable device (with short-circuit isolator) installed as another element inside the loop. The Relay and technical signal Module is placed in a rectangular, head-resistant ABS box.	8531/18%	7,125.00
13.	LG-MYOA	<b>Input/output Module</b> Microprocessor based algorithmic element installed as another element inside the loop (It is not addressable – there is no need to configure this element). The element is feed from the loop connection	8531/18%	11,700.00
14.	LG-KABY	<b>Loop Isolator Module</b> Microprocessor based digital and addressable device (with short-circuit isolator) installed as another element inside the loop. The sounder is made of in ABS heat-resistant plastic red color. Standard configuration of the light signal at the base of the sounder SIRAY+BSLC according to EN 54-23	8531/18%	5,625.00
15.	LG-SIRAY	Addressable <b>Loop Sounder</b> • 32 Selectable Tones • Low Current Consumption • Automatic Synchronization	8531/18%	12,375.00
16.	LG-SIRAYL	Addressable <b>Loop Sounder and Flasher</b> • 32 Selectable Tones • Low Current Consumption • Automatic Synchronization	8531/18%	12,600.00

#### CO<sub>2</sub> GAS CARTRIDGE FOR FIRE EXTINGUISHERS (IS: 4947)

S. No.	LG-CODE	DESCRIPTION	HSN CODE / GST RATE	RATES (INR)
1.	LG-2506	CO <sub>2</sub> Gas cartridge ISI Marked IS 4947. Capacity 60gms. <b>Brand LIFEGUARD</b>	8424/18%	500.00
2.	LG-2512	CO <sub>2</sub> Gas cartridge ISI Marked IS 4947. Capacity 120gms. <b>Brand LIFEGUARD</b>	8424/18%	600.00
3.	LG-2520	CO <sub>2</sub> Gas cartridge ISI Marked IS 4947. Capacity 200gms. <b>Brand LIFEGUARD</b>	8424/18%	700.00
4.	LG-2530	CO <sub>2</sub> Gas cartridge Capacity 300gms. <b>Brand LIFEGUARD</b>	8424/18%	1,000.00
5.	LG-2550	CO <sub>2</sub> Gas cartridge Capacity 500gms. <b>Brand LIFEGUARD</b>	8424/18%	1,375.00

#### FIRE FIGHTING CHEMICAL AND REFILLS

S. No.	LG- CODE	DESCRIPTION	HSN CODE / GST RATE	RATES (INR)
1.	LG-553	Dry powder for A, B&C Class of fire ISI marked MAP 50% IS:4308	8424/18%	125.00 Per Kg
2.	LG-553	Dry powder for A, B&C Class of fire ISI marked MAP 90%	8424/18%	400.00 Per Kg
3.	LG-720	Dry powder for A, B&C Class of fire UL listed MAP 90%. <b>Brand LIFEGUARD</b>	8424/18%	650.00 Per Kg
4.	LG-552	Dry powder for B&C Class of fire ISI marked IS:4308	8424/18%	60.00 Per Kg
5.	LG-553A	Dry powder for A, B&C Class of fire	8424/18%	162.50 Per Kg
6.	LG-551	Foam concentrated for producing mechanical foam for firefighting type -6%. Capacity 540 ml.	8424/18%	150.00 Each
7.	LG-551A	Foam concentrated for producing mechanical foam for firefighting type -6%. Capacity 3litre.	8424/18%	650.00 Each
8.	LG-551B	Foam concentrated for producing mechanical foam for firefighting type -6%. Capacity 20litre.	8424/18%	2500.00 Each

9.	LG-551C	Foam concentrated for producing mechanical foam for firefighting type -3%. Capacity 540 ml.	8424/18%	200.00 Each
10.	LG-551D	Foam concentrated for producing mechanical foam for firefighting type -3%. Capacity 3litre.	8424/18%	750.00 Each
11.	LG-551E	Foam concentrated for producing mechanical foam for firefighting type -3%. Capacity 20litre.	8424/18%	2,750.0Each
12.	LG-551F	Foam concentrated for producing mechanical foam for firefighting UL Listed	8424/18%	245.00 Per liter

**MISCELLANEOUS FIRE FIGHTING ACCESSORIES**

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-549	<b>Fire Rescue Kit</b> , Equipped with emergency response material, contained in a mild steel box (460X380X165)mm with texture finish to with-stand all weather conditions containing 1 whistle, 1 safety torch, 1 Fire blanket, 1 Respiratory Oxygen Reserver set for Resuscitator with Multi Gas Filters, 1 Smoke mask & 1 Fireman Axe. <b>Brand LIFEGUARD</b>	7310/18%	70,000.00
2.	LG-525P	<b>Heavy-Duty Leak-Proof ISI Marked Fire Bucket</b> made of Mild Steel conforming IS 2546:1974 Capacity 10 Liter. <b>Brand LIFEGUARD</b>	7310/18%	1,850.00
3.	LG-525	Fire Bucket MS Capacity 9/ 10 liter. <b>Brand LIFEGUARD</b>	7310/18%	700.00
4.	LG-525C	Fire Bucket Commercial.	7310/18%	400.00
5.	LG-525A	Fire Bucket Stand suitable for 4 buckets. <b>Brand LIFEGUARD</b>	7308/18%	1,500.00
6.	LG-525B	Fire Bucket Stand suitable for 6 buckets. <b>Brand LIFEGUARD</b>	7308/18%	1,750.00
7.	LG-525A	Fire Bucket Stand with Canopy suitable for 4 buckets. <b>Brand LIFEGUARD</b>	7308/18%	5,250.00
8.	LG-525B	Fire Bucket Stand with Canopy suitable for 6 buckets. <b>Brand LIFEGUARD</b>	7308/18%	6,125.00
9.	LG-534	Fire Extinguisher Stand. <b>Brand LIFEGUARD</b> 1. M.S. (Round Shape) 2. S.S. (Round Shape)	7308/18%	750.00 750.00
10.	LG-54007	Flexible Hose for sprinklers with fitting UL listed 700MM	7307/18%	1,250.00
11.	LG-54010	Flexible Hose for sprinklers with fitting UL listed 1000MM	7307/18%	1,350.00
12.	LG-54012	Flexible Hose for sprinklers with fitting UL listed 1200MM	7307/18%	1,450.00
13.	LG-54015	Flexible Hose for sprinklers with fitting UL listed 1500MM	7307/18%	1,625.00
14.	LG-54018	Flexible Hose for sprinklers with fitting UL listed 1800MM	7307/18%	2,100.00
15.	LG-538	Fireman axe	8205/18%	875.00
16.	LG-530	Fire hook without bamboos.	8205/18%	425.00
17.	LG-531	Fire beater without bamboos.	8205/18%	550.00
18.	LG-532	Shovel with wooden handle.	4417/12%	1,625.00
19.	LG-527A	Mobile Foam Unit with Variable Inline Inductor, Nozzle, 2 No's RRL Hose And 20litre X 4pc AFFF Foam. Complete in all respect as per PGC Drawing.	7310/18%	1,12,500.00
20.	LG-527B	M.S tank Mobile Foam Unit capacity 100 liter along with Inline inductor, nozzle, 2 No's RRL Hose. Complete in all respect.	7310/18%	1,20,000.00
21.	LG-527C	M.S tank Mobile Foam Unit capacity 200 liter along with Inline inductor, nozzle, 2 No's RRL Hose. Complete in all respect.	7310/18%	1,62,500.00
22.	LG-527D	S.S tank Mobile Foam Unit capacity 100 liter along with Inline inductor, nozzle, 2 No's RRL Hose. Complete in all respect.	7310/18%	1,55,000.00
23.	LG-527E	S.S tank Mobile Foam Unit capacity 200 liter along with Inline inductor, nozzle, 2 No's RRL Hose. Complete in all respect.	7310/18%	2,20,000.00
24.	LG-527A	G.M. Variable Inline Inductor with pickup tube & inbuilt NRV to foam inlet	7412/18%	26,250.00
25.	LG-518A	Electric siren 1/2 km 220 V <b>Brand LIFEGUARD</b>	8531/18%	3,750.00
26.	LG-518B	Electric siren 1 km 220 V <b>Brand LIFEGUARD</b>	8531/18%	5,500.00
27.	LG-518C	Electric siren 1 1/2 km 220 V <b>Brand LIFEGUARD</b>	8531/18%	9,000.00
28.	LG-518D	Electric siren 2 km 220 V Double Mounting <b>Brand LIFEGUARD</b>	8531/18%	13,750.00
29.	LG-519E	Electric siren 3 km 220 V Double Mounting <b>Brand LIFEGUARD</b>	8531/18%	18,000.00
30.	LG-519A	Hand operated siren 1/2 km <b>Brand LIFEGUARD</b>	8306/18%	7,000.00
31.	LG-519B	Hand operated siren 1 km <b>Brand LIFEGUARD</b>	8306/18%	8,750.00
32.	LG-519C	Hand operated siren 1 1/2 km with Stand <b>Brand LIFEGUARD</b>	8306/18%	17,500.00
33.	LG-543	Gum Boot	6405/18 %	1,400.00
34.	LG-524	Fireman Helmet	6506/18%	2,750.00

35.	LG-504	FB-10x with nozzle	8424/18%	13,500.00
36.	LG-505	FB-5x Nozzle pick-up tube	8424/18%	8,000.00
37.	LG-506	G.M. Dividing Breaching	7412/18%	18,750.00
38.	LG-507	G.M. Suction Strainer	7412/18%	16,500.00
39.	LG-508	G.M. Foot Valve Strainer	7412/18%	20,500.00
40.	LG-509	G.M. Suction Coupling	7412/18%	17,500.00
41.	LG-510	Revolving Branch	8424/18%	17,000.00
42.	LG-511	Fog Nozzle	8424/18%	19,250.00
43.	LG-512	Triple Purpose Nozzle	8424/18%	16,500.00
44.	LG-522	Hand Control Fast Action Nozzle	8424/18%	30,000.00
45.	LG-516	Jumbo Water Curtain Branch Nozzle (63 mm)	8424/18%	12,000.00
46.	LG-513	Double Male Coupling	7412/18%	4,500.00
47.	LG-514	Double Female Coupling	7412/18%	10,000.00
48.	LG-515A	Gun Metal Adaptor	7412/18%	3,500.00
49.	LG-515C	Stainless Steel Adaptor	7307/18%	2,500.00
50.	LG-529	G.M. Fire Bell	8306/18%	40,000.00
51.	LG-533	Rope Ladder Length 10Mtr	5609/12%	6,250.00
52.	LG-535	Fire Blanket	7019/18%	2,475.00
53.	----	Pressure Gauge Diaphragm Type	8424/18%	188.00
54.	----	ABC Valve Squeeze Grip Type	8424/18%	450.00
55.	LG-536	Pick Axe	4417/12%	1,000.00
56.	LG-523	Metal Detector	-	6,750.00
57.	LG-542	Reflective Jacket	-	875.00
58.	LG-544	Hose Binding Machine	8479/18%	55,000.00
59.	LG-547	Air Vessel with 8mm thick MS Sheet a) Size 250 X 1200 b) Size 250 X 2000 <b>Brand LIFEGUARD</b>	7310/18%	27,500.00 40,000.00
60.	LG-548	Flow Switch a) Usable line size 4" b) Usable line size 6"	9026/18%	11,500.00 14,000.00

**NOTE: - PLEASE REFER OUR CATALOGUE FOR LG-CODES AND THEIR CORRESPONDING PICTURES.**

**Terms & conditions**

1. This price list cancels all our previous price lists; it is not to be treated as MRP.
2. These above rates are FOR ex-works Delhi basis.
3. GST Rates shall be charged extra as applicable on individual items.
4. Warranty: 12 months from the date of Invoice/Delivery.
5. Delivery ex-stock/ within 5 weeks after receipt of confirmed order with advance payment.
6. All our transactions are subject to Delhi jurisdiction.
7. Payment 50% advance along with confirmed order & balance before Dispatch or L/C.
8. Late Payment will be subjected to additional charges of 18% per annum of interest.
9. If any Inspection is required same shall be conducted at our works only.
10. Additional amount shall be charged if inspection is required.
11. Loading/ Unloading will be in scope of Consignee after dispatch from works.
12. HSN code/GST rates may require verification before actual implementation.
13. Cost Implication of any Services upon any of the goods will be in Buyer's Scope.
14. Prices are subject to change without any prior notice.

For **United Fire Equipments Private Limited**  
sd/-  
Authorized Signatory